

JK-SP6041

OUTLINE DRAWING (Unit : mm)

SPECIFICATIONS

- Insertion Loss @ 1004Hz : Less than 1.0 dB.
- Attenuation Distortion @ 0.2~3.4KHz : ± 1.0 dB.
- Attenuation Distortion @ 3.4~4.0KHz : ± 1.5 dB.
- Delay Distortion @ 0.6~3.4KHz : Less than 200us.
- Delay Distortion @ 0.2~4.0KHz : Less than 250us.
- Return Loss @ 0.2~1.5KHz : Greater than 11 dB.
- Return Loss @ 1.5~2.0KHz : Greater than 10 dB.
- Return Loss @ 2.0~3.4KHz : Greater than 9 dB.
- Longitudinal Balance @ 0.2~1.0KHz : Greater than 58dB.
- Longitudinal Balance @ 1.0~3.0KHz : Greater than 58dB.
- Attenuation @ 30~300KHz : Greater than 65.0 dB.
(Input Level 10dBm)
- Attenuation @ 300~1104KHz : Greater than 55.0 dB.
(Input Level 10dBm)
- DC Resistance Between TIP-RING (WALL-PHONE):
Less than 40Ω . (120mA)
- Insulation Resistance Between TIP-RING
(L1-L2, L1-GND, L2-GND) : Greater than $10M\Omega$.
- ANSI, AnnexE, Type4 Type for JAPAN Standard.

FREQUENCY RESPONSE
